

























## E. PRODUCT GUIDE

<b>AS2458</b>  TAMROCK 3340028 Overall Height: 16.28 (414) Overall OD: 3.94 (100) End 1 ID: 0.63 (16) End 2 ID: 2.15 (55)	<b>AS2466</b>  INGERSOLL-RAND 93522902 Overall Height: 12.36 (314) End 1 OD: 7.56 (192) End 2 OD: 6.61 (168) End 1 ID: 4.80 (122)	<b>AS2475</b>  DEMAG 5482874 Overall Height: 8.35 (212) End 1 OD: 6.69 (170) End 2 OD: 5.28 (134) End 1 ID: 3.47 (88)
<b>AS2459</b>  DEMAG 10173774 Overall Height: 15.75 (400) End 1 OD: 13.78 (350) End 2 OD: 11.73 (298) End 1 ID: 8.62 (219)	<b>AS2467</b>  MANN & HUMMEL 4900050181 Overall Height: 24.09 (612) End 1 OD: 13.98 (355) End 2 OD: 11.73 (298) End 1 ID: 9.57 (243)	<b>AS2476</b>  DEMAG 13088474
<b>AS2460</b>  MANN & HUMMEL 4900050191 Overall Height: 20.16 (512) End 1 OD: 13.98 (355) End 2 OD: 11.73 (298) End 1 ID: 9.57 (243)	<b>AS2468</b>  ATLAS COPCO 1613839700 Overall Height: 7.09 (180) End 1 OD: 11.81 (300) End 2 OD: 6.61 (168) End 1 ID: 4.25 (108)	<b>AS2477</b>  ATLAS COPCO 2911007500 Overall Height: 11.32 (288) End 1 OD: 6.93 (176) End 2 OD: 6.69 (170) End 1 ID: 1.13 (29) End 2 ID: 1.76 (45)
<b>AS2461</b>  ATLAS COPCO 2911001900 Overall Height: 21.85 (555) End 1 OD: 15.75 (400) End 2 OD: 10.35 (263) End 1 ID: 6.54 (166)	<b>AS2469</b>  HYDROVANE 59180 Overall Height: 11.26 (286) Overall OD: 2.76 (70) End 1 ID: 1.06 (27) Thread Size: M8-INT	<b>AS2478</b>  INGERSOLL-RAND 92866508 Overall Height: 11.89 (302) End 1 OD: 6.97 (177) End 2 OD: 5.28 (134) End 1 ID: 3.47 (88)
<b>AS2462</b>  TAMROCK 3267728 Overall Height: 10.00 (254) Overall OD: 3.13 (80) End 1 ID: 1.65 (42)	<b>AS2470</b>  DEMAG 11427474 Overall Height: 20.24 (514) End 1 OD: 17.28 (439) End 2 OD: 15.67 (398) End 1 ID: 12.36 (314)	<b>BF1363</b> Mercedes A0004771302
<b>AS2463</b>  INGERSOLL-RAND 92725514 Overall Height: 20.47 (520) End 1 OD: 17.28 (439) End 2 OD: 15.67 (398) End 1 ID: 12.36 (314)	<b>AS2471</b>  ATLAS COPCO 1613692100 Overall Height: 6.81 (173) End 1 OD: 8.66 (220) End 2 OD: 5.28 (134) End 1 ID: 2.95 (75)	<b>BT8512</b> Liebherr 5612546, 7004209, Mann & Hummel WD9502
<b>AS2464</b>  MANN & HUMMEL 4930252131 Overall Height: 12.01 (305) End 1 OD: 7.87 (200) End 2 OD: 6.61 (168) End 1 ID: 4.25 (108)	<b>AS2472</b>  DEMAG 10012674 Overall Height: 6.30 (160) End 1 OD: 6.69 (170) End 2 OD: 5.28 (134) End 1 ID: 2.95 (75)	<b>Cooling System Aids</b> <b>CC2523</b> Fuel Sampling Kit 
<b>AS2465</b>  INGERSOLL-RAND 92765783 Overall Height: 19.69 (500) End 1 OD: 17.32 (440) End 2 OD: 11.73 (298) End 1 ID: 8.62 (219)	<b>AS2473</b>  INGERSOLL-RAND 92101153 Overall Height: 10.08 (256) End 1 OD: 12.01 (305) End 2 OD: 10.79 (274) End 1 ID: 8.27 (210)	<b>CC2524</b> Microbicide Testing Kit 
<b>AS2474</b> DAF 1686587	<b>CC2525</b> Monitor-Basic lube oil engine analysis kit 	<b>CC2526</b> Monitor oil analysis 





## E. PRODUCT GUIDE

	Monitor - Basic lube oil engine analysis kit with prepaid mailer	<b>CC2567</b> Compleat Heat Transfer Fluid EG Concentrate, 55 Gal. Drum	<b>CC2594</b> Fleet-Tech Winter Conditioner, 55 Gal. Drum/Not sold in EMEA
		<b>CC2568</b> Compleat Heat Transfer Fluid EG Premix 50/50, 55 Gal. Drum	<b>CC2595</b> Fleet-Tech Winter Conditioner Super Concentrate, 2.5 Gal. Jug/Not sold in EMEA
<b>CC2532</b>	Premium Oil; 15W-40 (25 Liters)	 <b>CC2569</b> Compleat Heat Transfer Fluid PG Concentrate, 55 Gal. Drum	<b>CC2596</b> Fleet-Tech Asphaltene Conditioner Concentrate, 2.5 Gal. Jug // DER E3241 sleeping
<b>CC2543</b>	Monitor - Extended lube oil drain analysis kit	<b>CC2570</b> Compleat Heat Transfer Fluid PG Premix 50/50, 55 Gal. Drum	<b>CC2597</b> Fleet-Tech Asphaltene Conditioner, Quart // DER E3243 sleeping
<b>CC2544</b>	Monitor - Engine failure lube oil analysis kit	 <b>CC2571</b> Compleat Heat Transfer Fluid EG Premix 60/40, 55 Gal. Drum	<b>CC2598</b> Fleet-Tech Asphaltene Conditioner, Pint
<b>CC2548</b>	Monitor - Engine lube oil and fuel dilution analysis kit	<b>CC2572</b> Compleat Heat Transfer Fluid PG Premix 60/40, 55 Gal. Drum	<b>CC2601</b> Restore, Alkaline cleaner for removing Silicate Gel Contains 3.785 Liters. Solder Corrosion and scale Repl. CC2610 in Europe. One gallon container.
<b>CC2549</b>	Fleet-Tech Asphaltene Conditioner, 5 Gal. Pail/Not sold in EMEA	<b>CC2573</b> Compleat Heat Transfer Fluid EG Premix 40/60, Bulk	
<b>CC2550</b>	Fleet-Tech™ Asphaltene Conditioner, 55 Gal. Drum/Not sold in EMEA	<b>CC2575</b> Base Booster, 1 Gal. Jug	<b>CC2602</b> Coolant Test Kit, 3-Way Test Strip, 50/bottle
<b>CC2551</b>	Universal EG Concentrate 6/1 Gal Jug		
		<b>CC2577</b> Compleat Heat Transfer Fluid PG Premix 40/60, Bulk	<b>CC2602A</b> Coolant Test Kit, 4 PK 3-Way Strips
<b>CC2552</b>	Fleet-Tech Winter Conditioner Concentrate, 5 Gal. Pail/Not sold in EMEA // DER E3244 sleeping	<b>CC2584</b> Stableguard Urea 32, Bulk	<b>CC2602B</b> Coolant Test Kit, 100 Single 3-Way Strips
<b>CC2553</b>	Fleet-Tech Winter Conditioner Concentrate, 55 Gal. Drum/Not sold in EMEA	<b>CC2585</b> Stableguard Urea 32, 330 Gal. Plastic Tote	<b>CC2602M</b> Coolant Test Kit, 3-Way Test Strip, 50/bottle - Metric Version
<b>CC2554</b>	Fleet-Tech Winter Conditioner Concentrate, Bulk/Not sold in EMEA	<b>CC2586</b> Stableguard Urea 32, 275 Gal. Disposable Tote	
<b>CC2556</b>	Universal Low Silicate EG Concentrate, 55 Gal. Drum	<b>CC2587</b> Stableguard Urea 32, 55 Gal. Plastic Drum	<b>CC2602AM</b> Coolant Test Kit, 4 PK 3-Way Strips - Metric Version
<b>CC2559</b>	Fleet-Tech Asphaltene Conditioner Concentrate, Bulk	<b>CC2588</b> Fleet-Tech Turbo Diesel Fuel Additive, Pint	
<b>CC2560</b>	Fleet-Tech Winter Conditioner Super Concentrate, Bulk/Not sold in EMEA	<b>CC2590</b> Fleet-Tech Winter Conditioner, Bulk/Not sold in EMEA	<b>CC2607B</b> Quik-Chek Condemnation Test Strips, 1 Pack Strip, 100/box
<b>CC2562C</b>	Compleat Heat Transfer Fluid EG Premix 50/50, Bulk	<b>CC2591</b> Fleet-Tech Winter Conditioner, Pint/Not sold in EMEA	
<b>CC2563C</b>	Compleat Heat Transfer Fluid PG Concentrate, Bulk	<b>CC2592</b> Fleet-Tech Winter Conditioner, Quart/Not sold in EMEA // DER E3331 sleeping	
<b>CC2564C</b>	Compleat Heat Transfer Fluid PG Premix 50/50, Bulk	<b>CC2593</b> Fleet-Tech Winter Conditioner, 5 Gal. Pail/Not sold in EMEA	
<b>CC2565C</b>	Compleat Heat Transfer Fluid EG Premix 60/40, Bulk		
<b>CC2566C</b>	Compleat Heat Transfer Fluid PG Premix 60/40, Bulk		


















## E. PRODUCT GUIDE

<p><b>CC2607C</b> Quik-Chek Condemnation Test Strips, 25/box</p> 	<p><b>CC2663</b> Fleet-Tech Microbicide, 1 Gal. Jug</p>	<p><b>CC2696</b> Fleet-Tech Asphaltene Conditioner, 2.5 Gal. Jugs, 1 Skid (72 Jugs)</p>
<p><b>CC2609</b> Water-Chek™ Test Strip, 100/box</p> 	<p><b>CC2663M</b> Fleet-Tech Biocide 4 Liter - Single - European Market</p> 	<p><b>CC2697</b> Fleet-Tech Asphaltene Conditioner, Quart, 1 Skid (720 Quarts)</p>
<p><b>CC2610</b> Restore Cleaner, 1 Gal. Jug</p> 	<p><b>CC2674</b> Fleetcool EG Recycled Premix 50/50, Bulk</p>	<p><b>CC2698</b> Fleet-Tech Asphaltene Conditioner, Pint, 1 Skid (960 Pints)</p>
<p><b>CC2611</b> Restore™ Cleaner, 5 Gal. Pail</p> 	<p><b>CC2675</b> Fleetcool EG Recycled Premix 50/50, 55 Gal. Drum</p> 	<p><b>CC2699</b> Fleet-Tech Turbo Diesel Fuel Additive in pint size for pallet quantity 960 pints</p>
<p><b>CC2612</b> Restore™ Cleaner, 55 Gal. Drum</p> 	<p><b>CC2677</b> Universal Premix 50/50 Recycled, Bulk</p>	<p><b>CC2700</b> Monitor C - Coolant/ heat transfer fluid analysis kit</p>
<p><b>CC2637</b> Restore Plus Cleaner, 55 Gal. Drum</p>	<p><b>CC2678</b> Universal Premix 50/50 Recycled, 55 Gal. Drum</p> 	<p><b>CC2706</b> Monitor C - Coolant/ heat transfer fluid analysis kit</p> 
<p><b>CC2638</b> Restore Plus Cleaner, 1 Gal. Jug</p> 	<p><b>CC2682</b> Flash Rust Inhibitor DCA-DX 55 Gallon Drum</p>	<p><b>CC2714</b> Flash Rust Inhibitor DCA-DX 275 Gallon Tote</p>
<p><b>CC2650</b> For Upgrade, use CC2651 Monitor - Diesel fuel Go/No-Go analysis kit</p>	<p><b>CC2683</b> Flash Rust Inhibitor DCA-DX 5 Gallon Pail</p>	<p><b>CC2717</b> Coolant Test Kit Monitor for US and Canada</p>
<p><b>CC2651</b> Upgrade of CC2650 Monitor fuel analysis Diesel Fuel Quality Analysis will tell you if your diesel fuel meets ASTM D975 #2 diesel specifications.</p> 	<p><b>CC2684</b> Flash Rust Inhibitor DCA-DX Gallon</p>	<p><b>CC2720C</b> EG Concentrate Bulk</p>
<p><b>CC2661</b> Fleet-Tech Microbicide, Quart</p>	<p><b>CC2688</b> Flash Rust Inhibitor DCA-DX Quart</p>	<p><b>CC2721C</b> EG Premix 60/40 Bulk</p>
<p><b>CC2661M</b> Fleet-tech Biocide 1 Liter - European Market</p> 	<p><b>CC2689</b> Fleet-Tech Asphaltene Conditioner, 5 Gal. Pail, 1 Skid (36 Pails)</p>	<p><b>CC2722C</b> EG Premix 50/50 Bulk</p>
	<p><b>CC2690</b> Fleet-Tech Asphaltene Conditioner, 55 Gal. Drum, 1 Skid (4 Drums)</p>	<p><b>CC2727</b> Compleat EG Concentrate (5 gal. pail) Use CC2847 ES Compleat EG Concentrate in North America.</p>
	<p><b>CC2691</b> Fleet-Tech Winter Conditioner, Pint, 1 Skid (960 Pints)</p>	<p><b>CC2728</b> Compleat EG 50/50 Premix (5 gal. pail). Use CC2848 ES Compleat EG Premix in North America.</p>
	<p><b>CC2692</b> Fleet-Tech Winter Conditioner, Quart, 1 Skid (720 Quarts)</p>	<p><b>CC2729</b> Compleat PG Concentrate (5 gal. pail). Use CC2849 ES Compleat PG Concentrate in North America.</p>
	<p><b>CC2693</b> Fleet-Tech Winter Conditioner, 5 Gal. Pail, 1 Skid (36 Pails)</p>	<p><b>CC2730</b> Compleat PG 50/50 Premix (5 gal. pail). Use CC2850 ES Compleat PG Premix in North America.</p>
	<p><b>CC2694</b> Fleet-Tech Winter Conditioner, 55 Gal. Drum, 1 Skid (4 Drums)</p>	<p><b>CC2739</b> Fleetcool EX EG Concentrate, Bulk</p>
	<p><b>CC2695</b> Fleet-Tech Winter Conditioner, 2.5 Gal. Jug, 1 Skid (72 Jugs)</p>	<p><b>CC2740</b> Fleetcool EX EG Concentrate, 275 Gal. Tote</p> 
		<p><b>CC2741</b> Fleetcool EX EG Concentrate, 55 Gal. Drum</p>
		<p><b>CC2742</b> Fleetcool EX EG Concentrate, 6/1 Gal. Jug</p> 

## E. PRODUCT GUIDE

CC2743	Fleetcool EX EG Premix 50/50, Bulk	CC2773	Platinum Plus DFX-DPF Fuel Borne Catalyst Gallon	CC2792	Compleat Propylene Glycol 60/40 Premix Antifreeze Coolant - 55 gallon drum-- Superseded by ES Compleat PG Premix 60/40 in North America
CC2743W	Fleetcool EX EG Premix- Bulk	CC2777	ES Optimax™ Extender, Pint	CC2799C	Compleat EG Concentrate Bulk
CC2744	Fleetcool EX EG Premix 50/50, Tote			CC2802	Uses service part: 3899452S Monitor - Fluid sampling vacuum pump tool kit
CC2745	Fleetcool EX EG Premix 50/50, Drum	CC2779	ES Optimax Extender, Quart		
		CC2780	ES Optimax EG Concentrate, 6/1 Gal. Jug	CC2806	Uses service part: 3930708S Refractometer
CC2746	Fleetcool EX EG Premix 50/50, 6/1 Gal. Jug				
CC2747M	ES Compleat EG Concentrate - 5L	CC2782	ES Optimax EG Concentrate, 55 Gal. Drum	CC2817	Flash Rust Inhibitor DCA DX Bulk
CC2748M	ES Compleat EG 50/50 Premix - 5L			CC2820	ES Compleat EG Concentrate, 6/1 Gal. Jug
CC2749M	ES Compleat EG Concentrate - 20L	CC2783	ES Optimax EG Concentrate , 275 Gal. Tote		
CC2750M	ES Compleat EG 50/50 Premix - 20L			CC2821	ES Compleat EG Concentrate, 55 Gal. Drum
CC2751M	ES Compleat PG Concentrate - 5L	CC2784	ES Optimax EG Concentrate, Bulk	CC2821M	ES Compleat EG Concentrate - 208L
CC2752M	ES Compleat PG 50/50 Premix - 5L	CC2785	ES Optimax EG Premix 50/50, 6/1 Gal. Jug	CC2822C	ES Compleat EG Concentrate, Bulk
CC2753M	ES Compleat PG Concentrate - 20L			CC2822M	ES Compleat EG bulk Concentrate
CC2754M	ES Compleat PG 50/50 Premix - 20L	CC2787	ES Optimax EG Premix 50/50, Drum	CC2823	Uses service part: 3918034S ES Compleat EG Concentrate, 275 Gal. Tote
CC2757	Universal Light Duty PG Concentrate, 6/1 Gal. (No DCA4)			CC2825	ES Compleat EG Premix 50/50, 6/1 Gal. Jug
CC2758	Universal Light Duty PG Concentrate, 55 Gal. Drum (No DCA4)	CC2788	ES Optimax EG Premix 50/50, Tote		
CC2765	Fleetcool EX Extender- 1 Quart			CC2826	ES Compleat EG Premix 50/50, 55 Gal. Drum
		CC2789	ES Optimax EG Premix 50/50, Bulk	CC2826M	ES Compleat EG 50/50 Premix - 208L
CC2766	Platinum Plus DFX Fuel Borne Catalyst 5 Gallon Pail	CC2790	ES Optimax EG Premix 60/40, Tote	CC2827	ES Compleat EG Premix 50/50, Bulk
CC2767	Platinum Plus DFX Fuel Borne Catalyst Gallon			CC2827M	ES Compleat EG - 50/50 Premix - bulk
CC2770	ES Optimax EG Premix 60/40, 55 Gallon Drum				
CC2771	Platinum Plus DFX Fuel Borne Catalyst 55 gallon Drum				
CC2772	Platinum Plus DFX-DPF Fuel Borne Catalyst 5 Gallon Pail				



## E. PRODUCT GUIDE


	<b>CC2830</b> ES Compleat PG Concentrate, 6/1 Gal. Jug		<b>CC2842</b> ES Extender, 5 Gal. Pail	<b>CC2859</b> Uses service part: 3918034S Compleat EG 50/50 Premix (275 gal disposable tote). Use CC2834 ES Compleat EG Premix in North America
<b>CC2831</b>	ES Compleat PG Concentrate, 55 Gal. Drum	<b>CC2843</b>	ES Extender, Pint	<b>CC2860</b> Uses service part: 3918034S Compleat PG Concentrate (275 gal disposable tote). Use CC2833 ES Compleat PG Concentrate in North America
<b>CC2831M</b>	ES Compleat PG Concentrate - 208L		<b>CC2847</b>	<b>CC2861</b> Uses service part: 3918034S Compleat PG 50/50 Premix (275 gal disposable tote). Use CC2836 ES Compleat PG Premix in North America.
<b>CC2832C</b>	ES Compleat PG Concentrate, Bulk	<b>CC2847</b>	ES Compleat EG Concentrate, 5 Gal. Pail	<b>CC2862</b> ES Compleat EG Premix 60/40, Bulk
<b>CC2832M</b>	ES Compleat PG Concentrate bulk		<b>CC2848</b>	<b>CC2863</b> ES Compleat EG Premix 60/40, 55 Gal. Drum
<b>CC2833</b>	Uses service part: 3918034S ES Compleat PG Concentrate, 275 Gal. Tote		<b>CC2848</b>	<b>CC2864</b> ES Compleat PG Premix 60/40, Bulk
	<b>CC2834</b> Uses service part: 3918034S ES Compleat EG Premix 50/50, 275 Gal. Tote		<b>CC2849</b>	<b>CC2865</b> ES Compleat PG Premix 60/40, 55 Gal. Drum
	<b>CC2835</b> ES Compleat PG Premix 50/50, 6/1 Gal. Jug		<b>CC2850</b>	<b>CC2866</b> 20,000ltr Bulk PGPlus Premix Coolant
	<b>CC2836</b> ES Compleat PG Premix 50/50, 55 Gal. Drum		<b>CC2850</b>	<b>CC2867</b> 1,000ltr PGPlus Premix Coolant
<b>CC2836M</b>	ES Compleat PG - 50/50 Premix - 208L		<b>CC2851M</b>	<b>CC2868</b> 208ltr PGPlus Premix Coolant
<b>CC2837C</b>	ES Compleat PG Premix 50/50, Bulk		<b>CC2851M</b>	<b>CC2869</b> 20ltr PGPlus Premix Coolant
<b>CC2837M</b>	ES Compleat PG 50/50 Premix bulk		<b>CC2852M</b>	
<b>CC2838</b>	Uses service part: 3918034S ES Compleat PG Premix 50/50, 275 Gal. Tote	<b>CC2853M</b>	<b>CC2853M</b>	<b>CC2870</b> 4ltr PGPlus Premix Coolant
	<b>CC2840</b> ES Extender, Quart	<b>CC2854M</b>	<b>CC2854M</b>	
<b>CC2841</b>	ES Extender, 55 Gal. Drum	<b>CC2858</b>	<b>CC2858</b>	<b>CC2872</b> ES Compleat PG Premix 60/40, 275 Gal. Tote
				<b>CC2878</b> Fleetcool EG Concentrate Gallon

## E. PRODUCT GUIDE


CC2883C	EG Fleetcool Concentrate Bulk
CC2885	EG Fleetcool Concentrate (55 Gallon Drum)
CC2891	Monitor - Engine lube oil viscosity analysis kit
	
CC2895C	Compleat PG Concentrate Bulk
CC2896C	Compleat PG Premix Bulk
CC2899C	Compleat EG Premix Bulk
CC8948	Can
CC8951	ES Complete EG 40/60 275 Gallon Tote


### Centrifuge Lube Filters


CH41100	Uses service part: 3935261S, 3935262S, 3935293S, 3939604S, CS41005 Centrifugal By-Pass Lube Filter
	
	Overall Height: 11.31 (287) Assisted Drain: NO Overall Length: 6.53 (166) Overall Width: 7.38 (187) Thread Inlet: M22 X 1.5-6G INT Thread Outlet: 1 5/8-12 UN-2B
CH41101	Uses service part: 3935262S, 3940750S, 3940756S, 3941519S, 3943071S, CS41007 Gpm Air-Assisted Drain Centrifuge
	
	Overall Height: 11.32 (288) Assisted Drain: YES Overall Length: 6.53 (166) Overall Width: 7.39 (188) Thread Inlet: M22 X 1.5-6H INT Thread Outlet: 1/2 NPT
CH41102	Filter used with 3944520S Uses service part: 3935262S, 3940750S, 3940756S, CS41007 Centrifugal By-Pass Lube Filter. Generic use for lube systems typically on diesel engines able to support 1 GPM bypass flow (supply air is not required on this unit.)
	Overall Height: 11.31 (287) Assisted Drain: NO Overall Length: 6.53 (166) Overall Width: 7.38 (187) Thread Inlet: M22 X 1.5-6H INT Thread Outlet: 1 5/8-12 UN-2B


CH41111	Filter used with 3951366S Uses service part: 3943871S, 3950689S, CS41011 Remote mounted with gravity drain.
	
	Overall Height: 14.30 (363) Assisted Drain: NO Overall Length: 6.53 (166) Overall Width: 7.38 (188) Thread Inlet: M22 X 1.5-6G INT Thread Outlet: 1 5/8-12 UN-2B


CH41112	Filter used with 3951367S Uses service part: 3940750S, 3940756S, 3941519S, 3943071S, 3943871S, 3950690S, CS41011 Remote-mount, air assisted centrifuge
	
	Overall Height: 14.28 (363) Assisted Drain: YES Overall Length: 6.53 (166) Overall Width: 7.38 (188) Thread Inlet: M22 X 1.5-6G INT Thread Outlet: 1 5/8-12 UN-2B


CH41113	Filter used with 3955640S Uses service part: 3943871S, 3950689S, CS41016 Remote mounted with gravity drain.
	
	Overall Height: 14.30 (363) Assisted Drain: NO Overall Length: 6.53 (166) Overall Width: 7.38 (188) Thread Inlet: M22 X 1.5-6G INT Thread Outlet: 1 5/8-12 UN-2B

CH41114	Filter used with 3955641S Uses service part: 3941519S, 3943071S, 3943871S, 3950690S, CS41016 Remote-mount, air assisted centrifuge
	
	Overall Height: 14.30 (363) Assisted Drain: NO Overall Length: 6.53 (166) Overall Width: 7.38 (188) Thread Inlet: M22 X 1.5-6G INT Thread Outlet: 1 5/8-12 UN-2B

CH44105	CUMMINS 3332056 Uses service part: 3894971S, 3894975S, 3894976S, 3894977S, 3915993S, 3915994S, 3915995S, 3916005S, 3916910S, 3916911S, 3917128S, 3917161S, CS44000 Uses Service gasket: 3894973S, 3894972S Centrifugal By-Pass Lube Filter
	
	Height: 14.50 (368) Base OD: 8.80 (224) Housing OD: 7.80 (198)

CH44110	Uses service part: 3894975S, 3894976S, 3915993S, 3915994S, 3915995S, 3916002S, 3916003S, 3916004S, 3916005S, 3916006S, 3916009S, 3916011S, 3916910S, 3916911S, 3917064S, 3917065S, CS44000 Uses Service gasket: 3894973S, 3894972S Centrifugal By-Pass Lube Filter
	
	Housing OD: 7.48 (190)


CH44115	Uses service part: 3894975S, 3894976S, 3915993S, 3915994S, 3915995S, 3916002S, 3916003S, 3916004S, 3916005S, 3916006S, 3916009S, 3916011S, 3916910S, 3916911S, 3917064S, 3917066S, CS44000 Uses Service gasket: 3894973S Centrifugal By-Pass Lube Filter
	
	Housing OD: 7.48 (190)


CH44120	Uses service part: 3894975S, 3894977S, 3915993S, 3915994S, 3915995S, 3916005S, 3916910S, 3916911S, 3917129S, CS44000 Uses Service gasket: 3894973S, 3894972S Centrifugal By-Pass Lube Filter - Side Drain
	
	Height: 15.10 (384) Base OD: 9.00 (229)


### ConeStaC

CS41000	MACK 57GC286 Filter used with 485GB3219D ConeStaC for Centrifugal By-Pass Filters
	
	Overall Height: 4.98 (127) Overall OD: 3.85 (98)




























CS41001	DAF 1376481
	
	Overall Height: 4.98 (127) Overall OD: 3.85 (98)

CS41002	ROLLS ROYCE OE45353
	
	Overall Height: 5.02 (127) Overall OD: 3.85 (98)

CS41003	RENAULT V.I. 5010437143
	
	Overall Height: 4.98 (127) Overall OD: 3.85 (98)

CS41004	RENAULT V.I. 5001853256
	
	Overall Height: 4.98 (127) Overall OD: 3.85 (98)

## E. PRODUCT GUIDE

<p><b>CS41005</b> MACK 236GB245M Used with CH41100</p>  <p>Overall Height: 4.98 (127) Overall OD: 3.85 (98)</p>	<p><b>CV50001</b> Enviroguard OCV Breather Assembly only for CV50108 System</p>	<p><b>CV50112</b> Enviroguard OCV System for 221-300 HP. Non-Cummins engine applications</p> 
<p><b>CS41007</b> Used with CH41101, CH41102 1 gpm version of CS41005- Identical except for the nozzle size which adjusts the flow rate.</p>  <p>Overall Height: 4.98 (127) Overall OD: 3.85 (98)</p>	<p><b>CV50002</b> Enviroguard OCV Breather Assembly only for CV50110 System</p>	<p><b>CV50113</b> Open crankcase ventilation (OCV). Use with International 466 &amp; 530 engines; Single impactor CV50006</p> 
<p><b>CS41008</b> Disposable Centrifuge Rotor</p>  <p>Overall Height: 5.78 (147) Overall OD: 3.88 (99)</p>	<p><b>CV50004</b> Enviroguard OCV Breather Assembly only for CV50111 System</p>	<p><b>CV50114</b> Open crankcase ventilation (OCV). Use with Cummins M11 engine; Single impactor CV50006</p> 
<p><b>CS41010</b> MACK 57GC2206</p>  <p>Gasket: 3933345 Overall Height: 7.44 (189) Overall OD: 4.29 (109)</p>	<p><b>CV50006</b> Enviroguard OCV System for all Cummins B, ISB, C, ISC, and L engines</p> 	<p><b>CV50115</b> Open crankcase ventilation (OCV). Use on Dodge Ram pickup truck with Cummins ISB engine. Model years 1998-2002; Single impactor CV50005</p> 
<p><b>CS41011</b> Used with CH41111, CH41112 2 gpm Service Rotor &amp; Gasket</p>  <p>Overall Height: 7.44 (189) Overall OD: 4.29 (109)</p>	<p><b>CV50015</b> Enviroguard OCV System for 1998-2002 Dodge Ram Turbo 5.9L engine applications</p> 	<p><b>CV50116</b> Open crankcase ventilation (OCV). Use with Cummins ISC &amp; ISL engines; Single impactor CV50006</p> 
<p><b>CS41013</b> INTERNATIONAL TRUCKS 1842825C91 Disposable Centrifuge Assembly. Applied on 2004 International 466 and 570 engines.</p>  <p>Overall Height: 7.44 (189) Overall OD: 4.29 (109)</p>	<p><b>CV50051</b> Enviroguard OCV Breather Assembly and bracket only for CV50203 System</p> 	<p><b>CV50117</b> Open crankcase ventilation (OCV). Use with Cummins ISB engine; Single impactor CV50005</p> 
<p><b>CS41016</b> Used with CH41113, CH41114 1 gpm Service Rotor &amp; Gasket</p>  <p>Overall Height: 7.44 (189) Overall OD: 4.29 (109)</p>	<p><b>CV50053</b> Enviroguard OCV Breather Assembly and bracket only for CV50204 System</p> 	<p><b>CV50200</b> Enviroguard OCV System for Cummins M11 engine applications Includes Bracket for Installation</p> 
<p><b>CS44000</b> Used with CH44110, CH44115, CH44120, CH44105 ConeStaC for Centrifugal By-Pass Filters</p>  <p>Largest OD: 5.72 (145) Largest ID: 1.51 (38) End 1 ID: 5.55 (141) End 2 ID: 5.42 (138)</p>	<p><b>CV50054</b> Enviroguard OCV Breather Assembly and bracket only for CV50205 System</p> 	<p><b>CV50201</b> Open crankcase ventilation (OCV). Use with Cummins N14 engine; Dual impactor CV50053. Includes mounting bracket</p> 
<p><b>CV50000</b> Enviroguard OCV Breather Assembly only for CV50109 System</p>	<p><b>CV50108</b> Enviroguard OCV System for 60-90 HP. Non-Cummins engine applications</p> 	<p><b>CV50202</b> Open crankcase ventilation (OCV). Use with Cummins ISX and QSX diesel engines. Dual impactor CV50053. Includes mounting bracket</p> 
	<p><b>CV50109</b> Enviroguard OCV System for 91-120 HP. Non-Cummins engine applications</p> 	<p><b>CV50203</b> Open crankcase ventilation (OCV). Use with diesel engine application between 301-400 HP; Dual impactor CV50051. Includes mounting bracket</p> 
	<p><b>CV50110</b> Enviroguard OCV System for 121-160 HP. Non-Cummins engine applications</p> 	
	<p><b>CV50111</b> Enviroguard OCV System for 161-220 HP. Non-Cummins engine applications</p> 	

## E. PRODUCT GUIDE

**CV50204** Open crankcase ventilation (OCV). Use with diesel engine application between 401-525 HP; Dual impactor CV50053. Includes mounting bracket



**CV50205** Open crankcase ventilation (OCV). Use with diesel engine application between 525-640 HP. Dual impactor CV50054. Includes mounting bracket



**CV50601** CUMMINS 3683918 OCV Element Assembly used on Cummins ISX/ISM engines.

**CV50603** CUMMINS 4937499 OCV Service Element used on Cummins ISC/ISL engines.

**CV51118** Kit consists of: Q618145 Drain assembly, LT32668 CCV Coalescer kit installation instructions, CV50612 Coalescer assembly, 3955875 CDR Valve assembly, Q158110 CDR assembly mounting bracket

**CV52000** CUMMINS 4932168, CHRYSLER 68002433AA OCV Breather Assembly used on Cummins ISB engines.

**CV52001** CUMMINS 4936636 OCV Breather Assembly used on Cummins ISB engines.



### Cooling System Aids

**DCA30L** DCA2, Pint



**DCA35L** DCA2, 1/2 Gal Jug

**DCA40L** DCA2, 1Gal Jug



**DCA45L** DCA2, 5 Gal. Pail



**DCA50L** DCA2, 55 Gal. Drum

**DCA60L** DCA4, Pint

**DCA65L** DCA4, 1/2 Gal Jug

**DCA70L** DCA4, 1Gal Jug



**DCA75L** DCA4 Pail

**DCA80L** DCA4, 55 Gal. Drum

### Fuel Filters

**FF101** CUMMINS 105211, CUMMINS 299101 Uses service part: 105208S



Gasket: 250382<sup>10</sup>, 250389<sup>10</sup>, 3844190, 3844191  
Overall Height: 4.85 (123)  
Overall OD: 3.97 (101)  
End 1 ID: 0.77 (20)

**FF102** CUMMINS 44758, CUMMINS 299102 For lube application use LF503



Gasket: 250420  
Overall Height: 5.95 (151)  
Overall OD: 3.95 (100)  
End 1 ID: 1.08 (27)

**FF103** CUMMINS 299103



Gasket: 250938  
Overall Height: 7.66 (195)  
Overall OD: 3.01 (76)  
End 1 ID: 1.04 (26)

**FF104** CUMMINS 138627 Filter used with 142784S, 212013S For Upgrade, use FF5334, FF105



Gasket: 255622, 3301519<sup>10</sup>  
Overall Height: 4.15 (105)  
Largest OD: 3.70 (94)  
Thread Size: 1-14 UNS-2B

**FF105** CUMMINS 154709 Filter used with 142784S, 212013S, 3911894S, 3930618S Is a short version of FF213 Uses service part: 154711S, 255622S Upgrade of FF104 For Upgrade, use FS1212, FF5332 Extended Life Version of FF104 w/o drain For Synthetic Media Version use FF5332



Gasket: 255622, 3301519<sup>10</sup>  
Overall Height: 5.41 (137)  
Largest OD: 3.70 (94)  
Thread Size: 1-14 UNS-2B

**FF105C** CUMMINS 202893 Filter used with 142784S Extended Life Version of FF104 w/ drain cock



Gasket: 255622, 3301519<sup>10</sup>  
Overall Height: 6.24 (159)  
Largest OD: 3.70 (94)  
Thread Size: 1-14 UNS-2B

**FF105D** CUMMINS 156172 Filter used with 142784S Uses service part: 156171S, 255622S Extended Life Version of FF104 w/ drain plug



Gasket: 255622, 3301519<sup>10</sup>  
Overall Height: 6.02 (153)  
Largest OD: 3.70 (94)  
Thread Size: 1-14 UNS-2B

**FF106** CASE A31222 Uses service part: 250394S Primary Fuel in some applications



Gasket: 250394, 250938, 254503<sup>11</sup>, 254504<sup>11</sup>, 3304298<sup>10</sup>  
Overall Height: 5.71 (145)  
Overall OD: 3.01 (76)  
End 1 ID: 1.04 (26)

**FF106A** CASE A31222 Sock Version of FF106



Overall Height: 6.00 (152)  
Overall OD: 3.00 (76)  
End 1 ID: 1.02 (26)

**FF107** MACK 237GB13 Uses service part: 250383, 250383S



Gasket: 250383  
Overall Height: 6.29 (160)  
Overall OD: 3.95 (100)  
End 1 ID: 0.91 (23)

**FF108** CUMMINS 139097, CUMMINS 256834 Uses service part: 151884S, 151940S, 250843S, 251081S, 251091S, 251129S, 251390S, 3302009S, 3303210S



Gasket: 250413<sup>10</sup>, 251390  
Overall Height: 9.98 (253)  
Overall OD: 5.83 (148)  
End 1 ID: 0.99 (25)

**FF109** FIAT-ALLIS 74056633, CASE A7627, GMC 5573261 Uses service part: 250394S



Gasket: 250394, 250938, 254503<sup>11</sup>  
Overall Height: 3.24 (82)  
Overall OD: 3.01 (76)  
End 1 ID: 1.04 (26)